

Related Pending Application

Related Case Serial No: 09/438,425

Related Case Filing Date: 11-12-99

CLAIMS:

1 - Rotating electromagnetic actuator with limited stroke, comprising at least 2N poles on the stator, N being a whole number, energized by at least one energizer coil and N magnetized parts on the rotor arranged in an air gap of thickness E wherein each magnetized part is juxtaposed with at least one ferromagnetic part with a thickness e between 0 and E, defining one or two air gaps with a total length of E-e.

2 - Rotating electromagnetic actuator as claimed in claim 1, preferably single-phase, wherein the width of one of the magnetized parts Y_s measured on its mean diameter is equal to

$$C+S+2E'$$

where C is the width of the angular arc travelled by the rotor on the mean diameter of the magnetized parts, S is the width measured on the mean diameter of the magnetized parts between two adjacent stator poles, E' is between E/2 and E,

$$\text{with} \\ \frac{C + 2E'}{E} > 3$$

and

$$\frac{L}{E} > 0.75, \text{ preferably } 0.8 < \frac{L}{E} < 0.9$$

L designates the thickness of a magnetized part in the direction of magnetization, in order to ensure a torque due to the current roughly constant along the length of the stroke and roughly proportional to the current.

3 - Rotating electromagnetic actuator as claimed in claim 1 wherein the interposed ferromagnetic parts of the mobile part have a thickness e in the direction of magnetization of the magnetized parts of thickness L, so that: $0 < e/L < 0.6$.

4 - Rotating electromagnetic actuator as claimed in at least one of the

preceding claims wherein the N magnetized parts are composed of several juxtaposed magnets.

5 - Rotating electromagnetic actuator as claimed in claim 1 wherein the stationary component (2) comprises a stator part with 2N polar parts (8, 9) shaped like a tubular sector, each surrounded by an energizer coil (10, 10').

6 - Rotating electromagnetic actuator as claimed in claim 1 wherein the stationary component (2) comprises a second stator part (32) symmetrical to the first stator part, also with 2N semi-annular polar parts each surrounded by an energizer coil (40, 40').

7 - Rotating electromagnetic actuator as claimed in claim 1 wherein the mobile component (1) is formed by a rotating yoke bearing N magnetized parts (3), magnetized axially, and N interposed ferromagnetic parts (4).

8 - Rotating electromagnetic actuator as claimed in claim 1 wherein the mobile component is tubular or semi-tubular in shape and bears N magnetized parts shaped like tiles, magnetized radially, and at least one interposed ferromagnetic part, and wherein the stationary component has 2N stator poles of semi-tubular shape.

9 - Rotating electromagnetic actuator as claimed in at least one of the preceding claims wherein the mobile component comprises N magnetized parts magnetized after being positioned on the mobile component.

10 - Rotating electromagnetic actuator as claimed in at least one of the preceding claims wherein the mobile component comprises N magnetized parts housed in cavities provided in the yoke (6) of the mobile component, the areas complementary to these cavities forming the interposed ferromagnetic parts.

11 - Rotating electromagnetic actuator as claimed in at least one of the preceding claims wherein the 2N ferromagnetic polar parts of the stator are connected

12

between them by saturable ferromagnetic isthmuses.